



Not Equivalent - Better!

SAVE TIME AND MONEY !

NOBURN FIRE CABLE IS THE FASTEST CABLE TO PREPARE FOR TERMINATION.

FIRE SYSTEM CABLES

NoBurn Plus Enhanced is approved and certified by LPCB & BASEC to fully meet the requirements of 'Enhanced' fire cables for use with UK fire systems. See details of all standards below. Manufactured entirely and only in the UK.

NoBurn cable is produced using the latest technology, materials and equipment. Every detail from start to finish is recorded and traceable, a quality batch and test number is printed on every reel, and time and date of manufacture printed along the entire length of the cable.

NoBurn cable cores are twisted during manufacture to provide the highest level of data protection, ideal for long cable runs and analogue addressable fire systems.

No troublesome multiple sheaths to strip:-

- All in one - Easy strip outer sheath
- No separate foil
- No additional fibre wraps
- No mica tape on conductors
- No additional core separators to remove

• Also suitable for

- | | |
|--|----------------|
| Emergency Lighting Standard | BS 5266-1:2011 |
| Voice Alarm Systems Standard | BS 5839-8:2013 |
| Voice Communication Standard | BS 5839-9:2013 |
| (Risk Assessment May Demand Mechanical Protection) | |
| Irish Emergency Lighting Standard | IS 3217:2013 |
| Irish Fire Alarm System Standard | IS 3218:2013 |



NoBurn cable has superb working flexibility but stays where you put it, reduced installation time and costs.



LPCB Ref. No. 682d/01



Licence No: 152/001

Features

- Easy to Install and Superb Working Flexibility
- Up to 12 Twists per metre for Data Protection
- Red & White Outer Sheaths Available
- 1.0mm², 1.5mm², 2.5mm² & 4.0mm² Conductors
- 100m, 200m, 500m and Special Lengths Available
- Copper / Co-polymer Foil Screen
- Low Smoke & Zero Halogen
- Voltage Rating 300v/500v
- Suitable for Zone 1 and Zone 2 Hazardous Area use
- Suitable for Air Conditioning, Computer Control & Lift Doors where Low Smoke & Zero Halogen is required
- Supplied on Robust Grey Plastic Reels - Clear Identification from Standard Fire Cable

Approved and Certified to meet

BS 5839-1:2013 Clause 26.2e	'Enhanced' Fire System Cable
BS 8519:2010 Category 2	Fire Cable Code of Practice
BS 7629-1:2008	Fire Cable Standard
BS 8434-2:2003+A2:2009 120 mins	• Fire, Mechanical Shock & Water - 120 mins @ 930°C (Water final 60 mins)
BS EN 50200:2006 PH30, PH60 & PH120	• Fire & Mechanical Shock - total of 120 mins @ 830°C (MS every 5 mins)
BS 6387:2013 Clause 6, 7 & 8 CWZ	• C - Fire only for 180 mins (3 hours) @ 950°C W - Fire & Water for 30 mins @ 650°C (Water final 15 mins) Z - Fire & Mechanical Shock for 15 mins @ 950°C (MS every 30 seconds)
BS EN 50267-2-1:1999	Halogen Emission Standard
BS EN 61034-2:2005	Low Smoke Standard


Specifications

LPCB & BASEC approved to	'Enhanced' Fire Cable Fire Resistance Standard Fire Resistance Standard Fire Resistance Standard Fire Resistance Standard Fire Resistance Standard Halogen Emission Standard Low Smoke Standard	BS 5839-1:2013 Clause 26.2e BS 8519:2010 Category 2 BS 8434-2:2003+A2:2009 120 mins BS EN 50200:2006 PH30, PH60 & PH120 BS 7629-1:2008 BS 6387:2013 Clause 6, 7 & 8 CWZ BS EN 50267-2-1:1999 BS EN 61034-2:2005
Designed to comply to	Emergency Lighting Voice Alarm Systems Standard Voice Communication Standard	BS 5266-1:2011 BS 5839-8:2013 BS 5839-9:2013
Materials	CPC (Earth) Conductors Core Installation Screening Outer Sheath	Tinned Annealed Copper Plain Annealed Copper Fire Resistant Silicone Copper Foil Low Smoke Halogen Free Thermoplastic
Working Voltage	Core to Core Core to CPC	500V 300V
Types	Outer Sheath Colours Number of Cores Inner Cores CSA	Red or White 2, 3 & 4 Core 1.0, 1.5, 2.5 & 4.0mm ² CSA
Resistance	1.0mm ² CSA 1.5mm ² CSA 2.5mm ² CSA 4.0mm ² CSA	18.1 Ohms / 1Km 12.1 Ohms / 1Km 7.41 Ohms / 1Km 4.61 Ohms / 1Km
Minimum Bend Radius	Radius = 6 x Diameter	
Operating Temp. Installation Temp.	Minimum/Maximum Minimum/Maximum	-40°C to +90°C, 0°C to +70°C
Voltage Drop (DC or Single Phase AC)	1.0mm ² CSA 1.5mm ² CSA 2.5mm ² CSA 4.0mm ² CSA	44 Ohms mV / A / m 29 Ohms mV / A / m 18 Ohms mV / A / m 11 Ohms mV / A / m
Approximate Overall Diameter	2 Core 3 Core 4 Core	1.0mm ² / 8.00mm 1.5mm ² / 8.20mm 2.5mm ² / 8.80mm 4.0mm ² / 10.20mm 1.0mm ² / 8.90mm 1.5mm ² / 9.90mm 2.5mm ² / 10.80mm 4.0mm ² / 13.10mm 1.0mm ² / 10.40mm 1.5mm ² / 11.10mm 2.5mm ² / 12.60mm 4.0mm ² / 15.00mm
Approximate Weights	2 Core with CPC 3 Core with CPC 4 Core with CPC	1.0mm ² 8.2 Kg / 100 m 1.5mm ² 9.7 Kg / 100 m 2.5mm ² 14.4 Kg / 100 m 4.0mm ² 24.0 Kg / 100 m 1.0mm ² 9.8 Kg / 100 m 1.5mm ² 13.2 Kg / 100 m 2.5mm ² 19.4 Kg / 100 m 4.0mm ² 28.0 Kg / 100 m 1.0mm ² 11.2 Kg / 100 m 1.5mm ² 14.8 Kg / 100 m 2.5mm ² 22.7 Kg / 100 m 4.0mm ² 50.0 Kg / 100 m
Current Rating	Cable Clipped (DC or Single Phase AC) Enclosed (DC or Single Phase AC)	1.0mm ² 15A 1.5mm ² 19.5A 2.5mm ² 27A 4.0mm ² 36A 1.0mm ² 13A 1.5mm ² 16.5A 2.5mm ² 23A 4.0mm ² 30A
Capacitance Rating	1.5mm ² CSA 2 Core & CPC } 3 Core & CPC } 4 Core & CPC ~ 2.5mm ² CSA 2 Core & CPC } 3 Core & CPC } 4 Core & CPC }	Core to Core - Average 70 pF/m Core to Screen - Average 125 pF/m Core to Core - Average 75 pF/m Core to Screen - Average 150 pF/m Core to Core - Average 85 pF/m Core to Screen - Average 155 pF/m
Warranty	Period Identification	10 Years from Date of Manufacture Date of Manufacture Marked On Cable

The Fastest Fire Cable to Install

Ventcroft NoBurn Plus is available in a variety of multiple core combinations all with CPC (circuit protection conductor).

100m, 200m, 500m reels and other special lengths are available.



Grey Plastic Reels for Clear Identification from 'Standard' Cable

- Installer Safe and Easy Handling •
- Better Reeling and Damage Resistant •
- Weather and Moisture Resistant •

Available with Red & White Sheaths Ex Stock. Black, Orange and other Sheath Colours Available - MOQ will apply.

Manufacturers Recommended Installation Guide Lines

Recommended metal clip spacing 300mm Horizontal
400mm Vertical

The type, spacing and requirement of additional fixings when laid in Cable Trays is optional & relative to local risk assessment.

Installation Temperatures:

Minimum installation Temperature 0°C
Maximum installation Temperature 70°C

Operating Temperature:

Minimum -40°C to Maximum +90°C.

The cable should not be flexed or bent when either the cable or operating temperature is below the recommended minimum or above the maximum recommended installation temperatures.

Minimum Bend Radius = 6 x Diameter

Plastic clips or ties must not be used as the sole means of support for fire cable.

